

### MODEL 00389

Behlman's 00389 COTS power supply is a highly reliable, switch mode units built for high-end industrial or Military applications. The 00389 can accept a three phase 115/200 VAC, 400 Hz input and can supply eight DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications, and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Unit is Base Plate cooled.

**INPUT** Input Transient protection per Mil-STD-704A  
115/200 VAC +/- 20%, 360-440 Hz

**OUTPUT:**

1. +5 VDC @ 20 A
2. -5.2 VDC @ 12.5 A
3. -2 VDC @ 10 A
4. +8.5 VDC @ 10.6 A
5. -8.5 VDC @ 3.5 A
6. +15 VDC @ 16.7 A
7. -15 VDC @ 1.7 A
8. +28 VDC @ 2.7 A

**Load Regulation:** 1.0% no load to full load at nominal line.  
**Line Regulation:** 0.1% for 10% line change.  
**PARD-Ripple & Noise:** 1% of output voltage p-p maximum. (0.1-10 MHz bandwidth)  
**Over voltage protection:** 120% max.  
**Short circuit protection:** Output voltage drops to less than 1 volt, with automatic recovery  
**Current Limit:** Constant current limited to 130% of rated current max.  
**Efficiency:** 75%.



**GENERAL CHARACTERISTICS- see O&C drawing 24015**

**Isolation**  
**Input to Output:** 1000 VDC  
**Input to Case:** 1000 VDC  
**Output to Case:** 200 VDC  
**Dimensional Data:** 12.00"L X 7.00"W X 2.38"H  
**Weight:** 6.4 lbs  
**Input:** CBM5W5M0000S-759.0 POSITRONIC  
**Output:** CBM24W7F2000S-759.0 POSITRONIC

**ENVIRONMENTAL:**

**Operating Temperature:** -40°C to 80°C base plate cooled  
**Storage Temperature:** -57°C to 85°C  
**MTBF** 125,000 @ 25 Degrees C base plate, Ground benign

**Designed to meet the following MIL Standards**

**Shock:** MIL-S-901; MIL-STD-810C  
**Vibration:** MIL-STD-167; MIL-STD-810C; RTCA/DO-160  
**Humidity:** MIL-STD-810C  
**EMI/EMC:** MIL-STD-461C/D; RTCA/DO-160. RE102 with proper shielding.  
**Input power:** MIL-STD-704A



[www.behlman.com](http://www.behlman.com)

**ORBIT POWER GROUP**  
**Behlman Electronics**

Headquarters:  
80 Cabot Court, Hauppauge, NY 11788  
631 435-0410 800 874-6727  
Fax: 631 951-4341

2363 Teller Road, Suite 108  
Newbury Park, CA 91320  
805 375-7046 800 456-2006  
Fax: 805 498-2147

[sales@behlman.com](mailto:sales@behlman.com)