



SQ300-12- 60
SQ300-12- 100
SQ300-12- 250

FEATURES

- SHELF OR PLUG-BOARD MOUNT
- HIGH OVERLOAD CAPACITY
- BUILT-IN SURGE PROTECTION
- CONSTANT FREQUENCY
- CONFORMS TO AAR RECOMMENDED PRACTICES

DC – AC SQUARE WAVE INVERTER FOR RAILROAD AND TRANSIT

Behlman's SQ300 Series is a rugged inverter that supplies 120 VAC from a 12 VDC source for continuous operation or standby operation of railroad signal equipment.

The input is from a nominal 13.2 V lead acid or nickel cadmium battery, which should have a low internal impedance. The output is a square wave with a fixed frequency, 60 Hz, 100 Hz or 250 Hz, +/- 1% regardless of load, input voltage or temperature.

The output voltage is proportional to the input voltage and the inverter has a high overload capacity of 110%. The SQ300 can be shelf mounted on supplied rubber feet or plug board mounted with optional bracket.

The inverters are designed to meet the rugged mechanical and environmental requirements of railroad and transit use.

INPUT

Voltage: 12 VDC +/- 20%, approximately 30 amps (nominal 13.2 V battery)

OUTPUT

Power: 300 VA
Waveform: Square wave
Voltage: 120 VAC +/- 5% isolated and floating. Proportional To input voltage.
Current: 2.5 Amps
Overload: 110%
Frequency: Constant Frequency +/- 1%
-60 60 Hz
-100 100 Hz
-250 250 Hz
Efficiency: 90% typical at full load

PROTECTIVE CIRCUITS

Input: Fuse with surge arrestor and lightning protection
Overload: Overload fault current electronically limited to protect load... power restored when overload is removed
Thermal: Internal temperature sensor shuts off output to prevent heat damage

MECHANICAL & ENVIRONMENTAL

Dimensions: High-strength shelf-mount chassis with optional plug-board mount
5"W X 8"H X 9.5"D
(12.7 cm x 20.3 cm x 24.1 cm)

Weight: 25 lbs (11.3kgs)

Input: AAR terminals on front
Output: AAR terminals on front
Operating Temperature: -40° to 160° F
(-40° to 71° C)
Humidity: Up to 95% non-condensing

OPTIONS: Contact factory for additional options

PB: Standard Plug-Board mount with two tabs at top and bottom



Shown with Option PB

www.behlman.com

ORBIT POWER GROUP
Behlman Electronics

Headquarters:
80 Cabot Court, Hauppauge, NY 11788
631 435-0410 800 874-6727
Fax: 631 951-4341

2363 Teller Road, Suite 108
Newbury Park, CA 91320
805 375-7046 800 456-2006
Fax: 805 498-2147

sales@behlman.com